

P-Type Perc

Singe Glass Mono-Facial TOPCon Solar Module

530~555W

Model: UL-***M-144HV

Maximum Efficiency: **21.48%**



Outstanding Mechanical load Resistance

2400 Pa wind load, 5400 Pa snow load



Great Durability Against Extreme Conditions

Passed salt mist corrosion test, ammonia corrosion test, dust & sand test, fire test, all certified by TUV



Lower LCOE

Lower shading and resistive loss Lower temperature coefficient





Anti-PID(potential induced degradation)

Passed anti-PID test under 85°C damp heat 85% relative humidity for 96 hours



Full-Scenario Resilience

Proven through rigorous resistance tests for salt mist, ammonia corrosion, sand & dust, and LeTID degradation



12 Year Product Warranty **2%** Power Degradation In The First Year

25 Year Linear Power Warranty **0.55%** Linear Power Degradation

IEC 61215, IEC 61730

ISO 9001: 2015(Quality management systems)

ISO 14001: 2015 (Environmental management systems)

ISO45001: 2018 (Occupational health and safety)

UNI 9177 Fire Test: Class 1



CEC Listed



Ulica Official Website

Add: No.238, Yunlin Middle Road, Gulin Town Haishu District, Ningbo, China PC

TEL: +86-574-28828999

Email: sales@ulsolar.com.cn

Module Type	UL-530M-144HV				UL-535M-144HV		UL-540M-144HV		UL-545M-144HV		UL-550M-144HV		UL-555M-144HV					
		STC*	NOCT*		STC*	NOCT*	STC*	NOCT*	STC*	NOCT*	STC*	NOCT*	STC*	NOCT*				
Maximum Power(Pmax)	W	530	397		535	436		540	440		545	408		550	412		555	416
Maximum Power Voltage(Vmp)	V	41.50	38.18		41.60	38.27		41.70	38.36		41.80	38.46		41.90	38.55		42.00	38.64
Maximum Power Current(Imp)	A	12.77	10.39		12.86	10.47		12.95	10.54		13.04	10.61		13.13	10.68		13.21	10.76
Open-circuit Current(Voc)	V	49.60	45.14		49.70	45.23		49.80	45.32		49.90	45.41		50.00	45.50		50.10	45.59
Short-circuit Current(Isc)	A	13.47	10.87		13.54	10.93		13.60	10.98		13.65	11.02		13.75	11.10		13.83	11.16
Module Efficiency STC	%	20.51			20.70		20.89		21.09		21.28		21.48					

OPERATING PARAMETERS

Operating Temperature	-40°C~85°C
Maximum system voltage	DC1500V(IEC)
Maximum series fuse rating	25A
Nominal operating cell temperature	43±2°C
Power tolerance	0~+5Watt

Temperature coefficients of Pmax	-0.34%/°C
Temperature coefficients of Voc	-0.265%/°C
Temperature coefficients of Isc	0.049%/°C

Cell Type	N-type TOPCon Mono Half Cell		
No.of cells	144(6×12×2)		
Dimensions	2278*1134*30mm		
Weight	26.3kg		
Front Glass	3.2mm,Anti-Reflection Coating,High Transmission,Low Iron,Tempered Glass		
Frame	Anodized Aluminium Alloy		
Junction Box	IP68,3diodes		
Connector	☒ MC4 Compatible:PV-UL608 or ☐ Original:MC4-EVO2 or ☐ others _____		
Cable Length (Including Connector)	4mm ² ☐ Short Cable:(+)400/(-)200mm or ☒ Long Cable:(+)1400/(-)1400mm or ☐ Customized Length _____		



10 Stack/40HQ
740Pcs/40HO

